



FEATURES

- 80 PLUS Platinum
- Internal Oring
- 94% Efficiency
- Cold Redundancy
- Operating Temperature 0 to 50 Degrees C
- AC Input 90 - 264Vac ; DC Input 180 - 300Vdc
- Application For Server, China Telecom
- Support PMBus 1.2
- N+1 Redundant

CDR-4011-1M1

- Dimension : 220 x 54.5 x 40 mm (D x W x H)
- Total Max Power : 400W



UL , cUL , CB , CE , CCC , BSMI , FCC Class A , CISPR Class A , RoHS

INPUT SPECIFICATIONS	
Input voltage	AC Input 90 - 264Vac / DC Input 180 - 300Vdc
Input frequency	50 - 60Hz
Input current	6.7 - 1.8A

GENERAL SPECIFICATIONS	
Hold-up time	12ms @ 75% Load
Efficiency	at least 94% @ 50% Load
MTBF	50,000 hours at 50 degree C

ENVIRONMENTAL SPECIFICATIONS	
Temperature	0 to 50 degree C Operating
Altitude	10,000 feet Operating
Relative humidity	20% to 90% RH Operating

OUTPUT SPECIFICATIONS		
Voltage	+12V	+5Vsb
Regulation	±5%	± 5%
Max Load	33A	3.0A
Ripple & Noise	120mVp-p	50mVp-p

